

12 Input x 16 Output Component Video Matrix

The Juneau switch is an 12 input, 16 output matrix switch, designed for switching and distributing high definition component video. This allows the centralization of all video source equipment, and allows those sources to be shared throughout a residence or commercial facility.



Features

- * HD Component video (YPbPr)
- * Full non-blocking matrix - All outputs can display the same signal, or different signals.
- * NeoTouch™ front panel - no moving parts to jam.
- * Multiple control inputs - RS-232, USB, IR detector (front) and wired IR (rear)
- * Highly visible Vacuum Fluorescent Display (VFD)
- * Separate front panel indicators for IR and RS232 activity
- * Front panel lockout, Front panel blackout

Specifications

Power Inlet: IEC 320-C14
 Input Voltage: 90-240VAC 50-60Hz, 8W typical
 Dimensions: Width: 17" Height: 3.45" Depth 10.5"
 (not including removable feet)
 Weight: 12 lbs
 Video Bandwidth: 140MHz+ (up to 1080p)
 RS-232: 9600 baud, full two way protocol
 USB: Slave device, Windows driver included, MAC and Linux drivers available, Installs as virtual COM port at 9600 baud
 Rear IR: 3.5mm mono jack for 5V or 12V blaster input, polarity insensitive

Designed and Manufactured in the USA by:

NeoPro
 1594 Fayette St.
 El Cajon, CA 92020
 619-258-2000 sales & support
 www.neoprointegrator.com
 619-258-2135 fax

For pricing contact your NeoPro integration dealer

